

AU- B1600 / B 2600



FEATURES

- 1/3" SONY Super Had CCD
- Built-In Fixed Lens
- Auto White Balance
- AGC, BLC, Flickerless
- Built-in IR LED & Sensor
- Min Illumination : Night (0 Lux, IR LED On)
- Weather Proof Housing
- 65 mm in Diameter (IP 65)

**High Resolution
600 TV Lines**

Optional Model

AU B-1300 : 420 TVL, 12VDC, 15 Mtr
AU B-2300 : 420 TVL, 12VDC, 30 Mtr

Accessory Included

- Mounting Brackets
- Lens
- Housing (Outdoor)

SPECIFICATIONS

Details	AU - B 1600	AU - B 2600
Signal System	PAL	
Scanning System	2:1 Interface	
Scanning Frequency (H)	15.625 KHz	
Scanning Frequency (V)	50 Hz	
Image Sensor	1/3" SONY Super Had CCD	
Total Pixels No	537 (H) X 597 (V) 320 K	
Effective Pixels No.	500 (H) X 582 (V) 290 K	
Horizontal Resolution	600 TV Lines	
Video Output	1.0 V p-p	
S/N Ratio	More than 50 dB (AGC Off)	
Lens	Fixed Lens {f = 6mm}	Fixed Lens {f = 6/12mm}
Min. Illumination	Day (0.1 Lux, Night 0 Lux IR LED On)	
R LED and Sensor	12 EA	34 EA
R LED Visible Range	Max 15 Mtrs	Max 30 Mtrs
White Balance	Auto	
AGC,BLC, Flickerless	On / Off	
Shutter Speed	1/50 ~ 1/100,000 Sec	
Supplied Voltage	12 VDC	
Power Consumption	MAX 6W / 0.5 A	
Weight	Approx 800 Gms	

Unit No. 422 / 423, Building No. 9, Jogani Industrial Estate, Off. V. N. Purav Marg, Chunabhatti (E), Mumbai 22
Ph: 022-24055001 / 2 Telefax: 022- 24055006 (M) 09833545257
Email: piyush@conceptequipments.com Web: www.conceptequipments.com

