AURIC
Rise above expectations

CONCEPT
EQUIPMENTS
DIGITAL SECURITY SOLUTIONS

AU- C 4500

FEATURES

- 1/3" SONY Super Had CCD
- Super High Resolution : 550 TVL
- Min Illumination : 0.1 Lux
- Auto White Balance
- Auto Gain Control
- Back Light Support
- Flickerless (On/Off)

Rear View

AU-C4500

OPTIONAL ACCESSORY

- Mounting Brackets
- Lens
- Housing (Outdoor / Indoor)
- Power Supply

SPECIFICATIONS

Details	AU - C 4500
Signal System	PAL
Scanning System	2:1 Interface
Scanning Frequency (H)	15.625 Khz
Scanning Frequency (V)	50 Hz
Image Sensor	1/3" SONY Super Had CCD
Sync System	Internal / External (Line-Lock)
Total Pixels No	795 (H) X 596 (V) 470 K
Effective Pixels No.	752 (H) X 582 (V) 440 K
Horizontal Resolution	550 TV Lines
Video Output Level	1.0 V p-p
S/N Ratio	More than 50 dB (AGC Off)
Lens Mount	C/CS Mount
Iris Mode	ELC / DC (slide Switch)
Min. Illumination	0.1 Lux
Digital Noise Reduction	AUTO
AGC	On / Off
BIC, Flickerless	On / Off
White Balance	AUTO
Electronic Shutter Speed	1/50 ~ 1/1,20,000 Sec
Operating Temperature	-10 C ~ + 50 C
Supplied Voltage	24V AC (2-V-28V) / 12 VDC (10V-15V)
Power Consumption / Weight	MAX 3W / Approx 430 G